

DATA SHEET

STEEL ARMOR

USAA



- The USSA bullet resistant steel panel is a single sheet ballistic steel. USSA steel wall armor is an economical choice for wall construction and ideal for structural armor. This material conforms to UL and NIJ standards.
- It is recommended for use in wall armor, judge's benches, counter protection and as finished opaque panels used in security storefronts.
- Standard size: 48 x 96 sheets. Custom sizes available.
- Standard finish: Prime paint finish.
- Optional Finishes: Insulated, Clad in Stainless steel, Bronze, Anodized-Painted Aluminum

PROTECTION, TESTING & STANDARDS

Product	Ballistic Protection	Nominal Thickness	Nominal Weight Sq. Ft.
USSA 1-3	Level 3 (UL) IIIA (NIJ)	1/4"	10.25 lbs.
USSA 4-8	Level 4, 5, 7, 8 (UL) III (NIJ)	5/16"	13.5 lbs.

OTHER IMPORTANT INFORMATION

Installation: US Bullet Proofing recommends that pilot holes be drilled in the USSA panel to accommodate hanging metal on stud walls. The use of ----- screws at 12" – 24" OC is desirable. To ensure complete protection at seams, we recommend incorporating 2" overlap strips of USSA or welded seams. Specialty equipment required for cutting, etc.

Disclaimer: In as much as U. S. Bullet Proofing has no control over the use to which others may put this material, it does not guarantee that the same results, as those described herein will be obtained. Nor does USBP guarantee the effectiveness or safety of any possible or suggested design as illustrated herein by any photograph, technical drawing and the like. Each user of products or design or both should make his own tests to determine the suitability of the product or design or both for his own particular use.