


DATA SHEET

ALUMINUM DOUBLE DOORS MODEL USAD1000 SERIES



- The USAD Door Series is shipped pre-glazed and factory assembled. The unit is available as a swinging or sliding door, interior or exterior application.
- The USAD1000 Door Series is constructed as a full-flush type unit. Construction consists of heavy-duty aluminum extrusion and 1/8" minimum wall thickness. The extrusions allow for the insertion of armor consistent with specified threat level. The door framing is constructed from extruded aluminum with ballistic inserts. Transparent and opaque panels are interchangeable to provide necessary design flexibility. Complimentary window construction allows for aesthetically uniform security application that is available in many style and finish options.
- Standard door hardware: Heavy-duty hinge, deadbolt lockset with cylinder, LCN closer and push/pull handles. Optional hardware is available; please consult factory for further information.
- Style options: Full-lite, double lite, half-lite, opaque, sidelites, transoms, man-trap configuration.
- Standard door size: 6' x 7' (custom sizes available)
- Standard frame: 2 1/2"W x 4 1/2"D (custom sizes available)
- Monumental stile (5 5/16") and narrow stile (3") available. Monumental stile will accept a wide range of hardware in commercial mortise locksets and rim-mounted exit devices.
- FEMA 361 Certified
- Standard finish: Clear or bronze anodized (custom kynar paint, brass cladding, stainless steel cladding available)

It is recommended that the door be used in conjunction with protected wall and window areas.

Each end user should determine the ballistic and forced entry threat to ensure the correct product selection to meet and exceed security needs.

Specifications are available upon request.